

2,000 - 03/2012. The descriptions and illustrations contained in the present brochure are not binding. FAAC reserves the right to undertake product technical modifications without prior notice.



S800H

24V underground hydraulic operator for residential and condo swing-leaf gates



DF Supply, Inc.
10050 Wellman Road
Streetsboro, OH 44241
(800) 878-7829
sales@dfsupplyinc.com



FAAC
Simply automatic.



24V UNDERGROUND HYDRAULIC OPERATOR FOR RESIDENTIAL AND CONDO SWING-LEAF GATES

- Continuous use
- Max weight of leaf (1760 lbs) (800 kg)
- Max width of leaf (13 ft) (4 m)
- Maximum anti-crushing safety and reverse function on obstacle thanks to the magnetic encoder.
- Built-in positive stops.
- HYBRID technology - combines the advantages of hydraulic technology with that of 24V: sturdiness, high performance, reliability over time, speed control.
- Built-in handles for ease of handling and installation.



E024U 24V BOARD



FEATURES:

- UL991 safety standard compliant
- Powerful and efficient Switching Power Supply
- Easy programming with trimmers and dip switches
- One pushbutton automatic self learning
- Self resetting fuses
- Stand By mode for efficient power use
- Built in battery backup

SPECIFICATIONS:

AC input ratings:	115V - 60Hz - 2.5A
Stand By Power:	4W
Motor Output Current:	7A each
Accessory Power:	24 Vdc - 500 mA
Operating Temperature:	-4 °F - + 131 °F



BUILT-IN POSITIVE STOPS

Makes installation of mechanical stops on the ground unnecessary, both for opening and closing.



MAGNETIC ENCODER

with built-in Bus 2Easy.



HYDRAULIC RELEASE SYSTEM

which can be operated from inside or outside the property using a coded key



SELF-BEARING STEEL HOUSING

with cataphoresis processing (possible to weld to pillars) or in stainless steel

AVAILABLE MODELS

Part Number	Description
108710	S800H 100° 24V In Ground Operator
108712	S800H 180° 24V In Ground Operator

S800H DIMENSIONS AND TECHNICAL SPECIFICATIONS

	S800H CBAC	S800H SB	S800H CBAC	S800H SB
Input Voltage	24 Vdc			
Nominal Power	60 W			
Max torque	450 lbf. ft			
Max angular speed	8,2°/s			
Operating ambient temperature	-40°F ÷ 131°F (-40°C - +55°C)			
Max opening angle			113° (S800H 100°)	187° (S800H 180°)
Protection class			IP 67	
Deceleration type			electronic	
Max leaf width			13 ft (4 m)	
Frequency of use			continuous	
Hydraulic lock	yes		yes	no
Max leaf weight			1760 lbs (800 Kg)	