







TELEPHONE ENTRY





SINGLE FAMILY

INTERCOM CONTROLLER



FEATURE	1802-EPD	1802	1803	1808	1810	1812 Plus	1816	1820
Memory Options Phone Numbers Entry Codes	100	1000	1000	1000	1000	1 Direct	1200 Max	1200 Max
						27 Dial Out	10 Dial Out	10 Dial Out
						50	N / A	N/A
Programmable Directory Codes	Yes, 1 to 4 Digits	Yes, 1 to 4 Digits	Yes, 1 to 4 Digits	Yes, 1 to 4 Digits	Yes, 1 to 4 Digits	N / A	Yes, 1 to 4 Digits	Yes, 1 to 4 Digits
Programmable Area Codes	15	10	10	10	10	N / A	N / A	N / A
Communication	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex
10 & 11 Digit Dialing	Yes	Yes	Yes	Yes	Yes	Yes	N / A	N / A
DTMF Tone Output After Call Answer	Yes	Yes	Yes	Yes	Yes	N / A	N / A	N / A
Relays	2	2	2	2	2	2	1	1
Time Clock	Yes	Yes	Yes	Yes	Yes	Yes	N / A	N / A
Entry Code Time Zone Restrictions	Yes	Yes	Yes	Yes	Yes	Yes	N / A	N / A
Flash Entry Code	Yes	Yes	Yes	Yes	Yes	Yes	N / A	N / A
Postal Lock Provision	Yes	Yes	Yes	Yes	Yes	No	No	No
Built-in Directory	Yes	No	No	Yes	Yes	No	No	No
LCD Programming Display	Yes	Yes	Yes	No	Yes	No	No	No
Power	16 VAC	16 VAC	16 VAC	16 VAC	16 VAC	16 VAC	16 VAC	16 VAC
Operating Temperature	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)
Mounting Styles	Surface Flush	Surface Flush	Surface Flush	Surface	Surface Flush	Surface, Curved Surface Flush, and Wall	Surface	Surface
Handset Available	No	No	Yes	No	Yes	No	No	No
CCTV Camera Option	No	No	Yes	Yes	Yes	Yes	No	No

PROGRAMMABLE



FEATURE	1833	1834	1835	1837
Memory Options Phone Numbers & Entry Codes	3000	3000	3000	3000
Card (Device) Codes	8000 max	N / A	8000 max	8000 max
PC Programming	Yes	Yes	Yes	Yes
Programmable Directory Codes	Yes, 1 - 4 Digits	Yes, 1 - 4 Digits	Yes, 1 - 4 Digits	Yes, 1 - 4 Digits
Programmable Area Codes	255	255	255	255
Programmable Facility Codes	10	10	10	10
Anti-Pass Back	Yes	No	Yes	Yes
Transaction Buffer	8000 Events	8000 Events	8000 Events	8000 Events
Live Transaction Capability	Yes	Yes	Yes	Yes
Security (Permission) Levels	31	N / A	31	31
Holiday Schedule	Yes	Yes	Yes	Yes
Elevator Control Capability	Yes	No	Yes	Yes
Communication	Full Duplex	Full Duplex	Full Duplex	Full Duplex
10 & 11 Digit Dialing	Yes	Yes	Yes	Yes
Relays	3	2	3	3
Tracker Expansion Capability	16 Doors Max	N / A	16 Doors Max	16 Doors Max
DTMF Tone Output After Call Answer	Yes	Yes	Yes	Yes
Database Import / Export Feature	Yes	Yes	Yes	Yes
Hold Open Time Zones	8	8	8	8
Built-in Directory	No	Single-Line LCD	Single-Line LCD	8-Line LCD
Call Button	No	Yes	Yes	Yes
Postal Lock Provision	Yes	Yes	Yes	Yes
Power	16 VAC	16 VAC	16 VAC	16 VAC
Operating Temperature	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)	10°F to 145°F (-12°C to 62°C)
Mounting Styles	Surface / Flush	Surface / Flush / Wall	Surface / Flush / Wall	Surface / Flush / Wall
Handset Available	Surface or Flush Mount Styles Only	Surface or Flush Mount Styles Only	Surface or Flush Mount Styles Only	No
CCTV Camera Option	Yes	Yes	Yes	Yes