

## **125 kHz PROXIMITY CREDENTIALS**



3milliD Corporation provides 125 kHz frequency proximity credentials that are ISO compliant and can be programmed with the leading proximity formats.

All conventional form factors are available including clamshell, fob, magstripe, adhesive disk and ISO card.

#### Highest Quality Credentials

**Quick Lead Times** 

Most Experienced RFID Team 3milliD takes great pride in the quality and reliability of its products and believes the quality of its products exceeds other vendors. We are committed to a positive customer experience and believe this will provide our customers with a strong return on their investment.



## www.3milliD.com

# D 3millID®

### **125 kHz PROXIMITY CREDENTIAL PART NUMBERS**

| 3millID <sup>®</sup> Part<br>Number |  |
|-------------------------------------|--|
| 3326-3M                             |  |
| 3386-3M                             |  |
| 3586-3M                             |  |
| 3336-3M                             |  |
| 3536-3M                             |  |
| 3349-3M                             |  |
| 3391-3M                             |  |
|                                     |  |

## **125 kHz PROXIMITY CREDENTIALS SPECIFICATIONS**

| Credential Type          | ISO CARD                              | CLAMSHELL                           | KEYFOB                       | DISC                    |
|--------------------------|---------------------------------------|-------------------------------------|------------------------------|-------------------------|
| Dimensions               | 3.37 x 2.125 x 0.03<br>inches         | 3.37 x 2.125 x 0.075<br>inches      | 1.44 x 1.18 x 0.25<br>inches | 35 mm                   |
| Weight                   | 0.212 oz.                             | 0.317 oz.                           | 0.15 oz.                     | 0.045 oz.               |
| Frequency                | 125 kHz                               | 125 kHz                             | 125 kHz                      | 125 kHz                 |
| Read Range*              | Up to 6 inches                        | Up to 6 inches                      | Up to 2.5 inches             | Up to 2 inches          |
| Slot Punch               | Vertical or<br>Horizontal             | Vertical                            | Keyring hole                 | None                    |
| Operating<br>Temperature | -50° to 160°F                         | -50° to 160°F                       | -15° to 165°F                | -50° to 160°F           |
| Material                 | PVC                                   | Hard shell: ABS<br>Cover label: PVC | ABS Plastic                  | PVC/Adhesive<br>Backing |
| Part Numbers             | 3386-3M, 3586-3M,<br>3336-3M, 3536-3M | 3326-3M                             | 3349-3M                      | 3391-3M                 |

#### OPTIONS

3milliD can provide the following options for your custom needs: \* Slot Punch (Vertical or Horizontal) \* Custom Artwork (Text or Graphic)

#### FORMATS

26 bit (similar to H10301) 35 bit (similar to C-1000) 37 bit (similar to H10302) 37 bit (similar to H10404) More formats available

3milliD credentials are comparable in performance and functionality to other part numbers referenced.



REV 20201123

