

# 811LMX / 813LMX 892LT / 894LT

Programmable DIP and Learning Remote Controls



Provide convenient access to gated communities, industrial facilities, and commercial sites with the right remote control solution for your application.

**PRODUCT GUIDE**

## Popular Features

### Learning Remote Controls

Easy Independent Button Programming allows for each button to be programmed with different frequency and codes.

Eliminate the need for multiple remotes when operating LiftMaster® Garage Door Openers, Gate Operators, Commercial Door Operators or myQ® Accessories.

Cloning capability of existing LiftMaster DIP Switch Remote Controls (61LM and 361LM) or a LiftMaster encrypted DIP Switch remote control (811LM) to any button as well as the 811LMX Programmable DIP in any of the above modes.

Flexible compatibility with direct programming to Security+ 2.0 and Security+ Rolling code technology for security and dependability.

### Programmable DIP Remote Controls

Both 811LMX and 813LMX allow up to 4096 unique codes with the 12-position DIP. 813LMX uniquely designed for open/close/stop functionality for commercial door applications.

Compatible with LiftMaster gate operators, commercial door operators and receivers. Can be programmed to the following DIP modes: Security+2.0 Encrypted DIP (default), legacy 315 MHz or legacy 390 MHz.

**LiftMaster**

POWERED BY myQ®

## Specifications

### 892LT

2-Button Security+ 2.0® Learning Remote Control

### 894LT

4-Button Security+ 2.0® Learning Remote Control

#### Compatibility

Code / frequency for direct programming:

- Security+ 2.0® – Default
- Security+® 315 MHz
- Security+ 390 MHz

Code / frequency for cloning 811LMX Programmable DIP (in the below modes):

- 811LM Encrypted DIP Switch
- 361LM DIP Switch 315 MHz
- 61LM DIP Switch 390 MHz

#### Power

Battery (included): AAA battery

#### Dimensions

3.2" W x 1.75" H x .07" D

#### Radio

- Security+ 2.0 (Default)
- Security+ 315 MHz
- Security+ 390 MHz
- Clone Capability: 811LM, 361LM, 61LM, 811LMX

#### Operating Temperature

-40 °F (-40 °C) to 149 °F (65 °C)

#### Shipping Weights

.16 lbs.

#### Carton Contents

Remote control, visor clip, instruction manual

#### Storage / Ship Temperature

-40 °F (-40 °C) to 185 °F (85 °C) @ 50% Rh

#### Warranty

1 Year Limited

### 811LMX\*

- Single Button Programmable DIP Remote Control

### 813LMX†

- 3-Button OCS (Open/Close/Stop) Programmable DIP Remote Control

#### Compatibility

Code / frequency for direct programming:

- Encrypted DIP (Default)
- 315 MHz DIP
- 390 MHz DIP

#### Power

Battery (included): Coin Cell 3V – CR2032 type

#### Dimensions

3.125" W x 1.75" H

#### Radio

- Security+ 2.0 Encrypted DIP (Default)
- 315 MHz DIP Switch
- 390 MHz DIP Switch

#### Operating Temperature

-40 °F (-40 °C) to 149 °F (65 °C)

#### Shipping Weights

.22 lbs.

#### Carton Contents

Remote control, visor clip, instruction manual

#### Storage / Ship Temperature

-40 °F (-40 °C) to 185 °F (85 °C) @ 50% Rh

#### Warranty

1 Year

\* Replaces 811LM, 361LM, 61LM, 61LMC Remote Controls providing the same functionality

† Replaces 813LM, 333LM, 33LM Remote Controls providing the same functionality

Visit [LiftMaster.com](https://www.liftmaster.com)

#### Inquiries

For Sales: 800.282.6225 | For Technical Support: 800.528.2806



© 2021 The Chamberlain Group LLC. All Rights Reserved.

LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group LLC.  
LMACENPGLMXLT 10/21