

# **PS-2420UL**

DC 24V Class II Power Supply



### I.T.E. POWER SUPPLY PS-2420

**INPUT** 

100-240V∼ 50/60Hz

110-140VA 1.2-0.65A

OUTPUT 24V === 2.0A

Model No. NU48-2240200-13















## **CAUTION:**

RISK OF ELECTRIC SHOCK DRY LOCATION USE ONLY NO SERVICEABLE PARTS INSIDE



### ATTENTION:

POUR UTILISATION À L'INTÉRIEUR SEULEMENT DOUBLE PÔLE FUSIBLE

VORSICHT: Doppel-Pole Fusing

本製品は当社製インターホンの専用電源です。 ほかの用途には使用しないでください。 This product is designed for exclusive use of Aiphone Intercom Systems. Do not use for other systems

Ce produit est conçu pour l'utilisation exclusive du systèmes d'interphone Aiphone. Ne pas utiliser pour d'autres systèmes.



LEI F6 MADE IN CHINA EL

V2

See the INSTALLATION MANUAL for proper selection of the power supply cord Voir le manuel d'installation pour le choix du cordon d'alimentation.

#### **DESCRIPTION:**

The PS-2420UL is a DC 24V Class II power supply used for Aiphone intercom applications.

This power power supply is UL and CSA listed and is designed for indoor use only.

#### PRODUCT APPLICATIONS:

The PS-2420UL can be used for the following Aiphone Communication systems:

- **AX Series**
- **GT Series**
- **IM Series**
- JP Series
- **KB** Series
- MC Series
- **NHX Series**

#### SPECIFICATIONS:

AC 100~240V 50/60Hz Power input:

DC 24V 2A Power output: Power consumption: 110~140VA

32~104°F (0~40°C) Temp. Rating: Wiring connection: Screw terminals Dimensions (HxWxD): 6-\%16" x 3-\%16" x 2"