

# Longse



## SPECIFICATION

|                          |  |                  |
|--------------------------|--|------------------|
| <b>Model NO.</b>         | LBE90THC5005XESL   | LBE90THC5005XESL |
| <b>Video Output Mode</b> | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps<br>TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; |                  |
| <b>Camera</b>            |  |                  |
| Image Sensor             | 1/2.8" SONY Starvis Back-illuminated CMOS sensor   |                  |
| Image Resolution         | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080  |                  |
| TV System                | PAL/NTSC   |                  |
| Electronic Shutter       | Auto   |                  |
| Minimum Illumination     | Color : 0.003 lux@F1.6, AGC ON; B/W : 0 lux with IR  |                  |
| Scanning System          | Progressive Scan   |                  |
| <b>Lens</b>              |  |                  |
| Focus Length             | 2.7-13.5mm   |                  |
| Focus Control            | Auto   |                  |
| Lens Type                | Auto   |                  |
| <b>Night Vision</b>      |  |                  |
| IR Cut Filter            | YES  |                  |
| Infrared LED             | 42μ x 6PCS   |                  |
| Infrared Distance        | 60M  |                  |
| IR Status                | AGC Auto Control   |                  |
| <b>Camera Features</b>   |  |                  |
| Starlight                | N/A  |                  |
| Day/Night                | YES  |                  |
| OSD Menu                 | YES  |                  |
| WDR                      | 120dB  |                  |
| UTC                      | YES  |                  |
| Noise Reduction          | 3DNR   |                  |
| Coaxial Audio            | N/A  |                  |
| White Balance            | AUTO / MANUAL  |                  |
| Gain Control             | AUTO   |                  |
| <b>General</b>           |  |                  |
| Housing                  | Main Body: Metal Cover: Plastic, IP67  |                  |
| Bracket                  | YES  |                  |
| Operation Temperature    | -10°C ~ +60°C RH95% Max  |                  |
| Storage Temperature      | -20°C ~ +60°C RH95% Max  |                  |
| Power Source             | DC12V±10%, 900mA   |                  |
| Dimension                | 179(W) x 90(H) x 90(D)mm   |                  |
| Weight                   | 1400g  |                  |