

## SureClose® Center Mount

CODE*	MODEL	DESCRIPTION	MOUNTING
75001113	SM S	Non Self-Closing Hinge	Aluminum Screw-on
75057113M	57 S	Hinge Closer	Aluminum Screw-on
75057123M	57SF S**	Safety Hinge Closer	Aluminum Screw-on
75108113M	108 S	Hinge Closer w/ Final Snap Action	Aluminum Screw-on
75108123M	108SF S**	Safety Hinge Closer w/ Final Snap Action	Aluminum Screw-on
75001114	SM W	Non Self-Closing Hinge	Steel Weld-on
75057114M	57 W	Hinge Closer	Steel Weld-on
75057124M	57SF W**	Safety Hinge Closer	Steel Weld-on
75108114M	108 W	Hinge Closer w/ Final Snap Action	Steel Weld-on
75108124M	108SF W**	Safety Hinge Closer w/ Final Snap Action	Steel Weld-on

  

HINGE COMBINATIONS	MAX SELF-CLOSING GATE WEIGHT
57 + SM	90 lb (40kg)
57+57	180 lb (80kg)
108 + SM	180 lb (80kg)
108 + 108	260 lb (120kg)

  

ACCESS CONTROL	WEIGHT CAPACITY
SM + SM	

**CAUTION:** Based on max. gate size 72"H x 40"W (1800x1000mm). For gates with greater HxW, or if weather conditions such as wind play a significant role, use hinge combinations with higher self-closing weight ratings. **CAUTION: A gate-stop MUST be installed when using SF models.** Gate MUST NOT be allowed to open past 90°. Doing so voids warranty.

\* Warranty conditions vary according to gate or door application and usage. See full Warranty details and limitations on D&D Technologies' website.  
 Gate mounting brackets included with hinge. Post-mounting brackets sold separately. Fasteners not included.  
**\*\*Use only "SF" model (safety) closers on pool/safety gates.** Hinges must be at least 36" (900mm) apart so they cannot be used as footholds by toddlers.

### Gate Function

■ Hold-open  
 Not for safety gates

■ Self-closing  
 Speed adjustable

■ Final snap-close action  
 For electric/coded locks

