

ELIKA[™]
ACCESS SYSTEMS

The only cellular and VoIP telephone entry system
with PTCRB, FCC, and mobile network certifications.



ELIKA 460 Telephone Entry System

FOUR COLOR OPTIONS TO CHOOSE FROM



SILVER
(STANDARD)



GUNMETAL



BRONZE



WHITE

ELIKA EXCLUSIVE FEATURES

WEB BASED APP

- Allows remote programming of the system and updates in real-time
- Compatible with Windows, MacOS, Linux, Chrome OS, iOS and Android operating systems

MULTIPLE WIRELESS COMMUNICATION OPTIONS

- Choose between a variety of options: 3G, 4G, and VoIP (Voice Over Internet Protocol) over Ethernet or Wireless

DAY / NIGHT DIGITAL CAMERA

- Digital camera captures an image of every event and stores it in its event log with a time stamp

FULLY CERTIFIED

- The Only Cellular and VoIP Telephone Entry System that is PTCRB, FCC, and Mobile Network Certified in the United States

ELIKA SMART CALL

- This feature allows up to 3 contact phone numbers per user

SOLAR READY

- Can be powered with standard 12 volt solar panel and battery

BUILT IN SURGE AND LIGHTNING STRIKE PROTECTION

- Protection up to 200 Million Watts

HARDWARE SETTINGS REMOTE ADJUSTMENT

- Sound and light settings adjustable remotely.

DIGITAL NOISE AND ECHO CANCELLATION

- Eliminates the need for feedback adjustment
- Ensure clear voice communication

OPTIONAL SERVICES

BATTERY BACKUP

- In the event of power loss, your telephone entry system will remain functional

DESIGN

FOUR COLOR OPTIONS

- Silver, White, Gunmetal, Bronze

BACKLIT KEYPAD

- Fully adjustable brightness level

COURTESY LIGHT

- Adds security and convenience under low light conditions

ILLUMINATED CALL BUTTON

- Clearly visible at night time

4 LINE LCD DISPLAY

- Allows the display to list up to 4 tenants at one time

ENCLOSURE COMPONENTS

STAINLESS STEEL KEYPAD

- Provides a longer lasting, more durable surface

DIGITAL MICROPHONE

- Ensures clear voice communication

PROTECTION

ELECTRICAL PROTECTION

- Short Circuit, Electrostatic Discharge, Reverse Polarity and Relay Contact protection

ALUMINUM ENCLOSURE

- UV powder coated provides additional protection against corrosion and weather elements

IP65 RATED ENCLOSURE

STANDARD FEATURES

WIEGAND READER INTERFACE

- Available port for Wiegand communication
- Standard 26 bit Wiegand input port

TIMERS

- Seven programmable timers, each with seven days of the week

INDIVIDUAL TIME ZONES

- For each code, Elika Smart Key, shared key and RFID/HID
- Individual call time schedule per phone number

HISTORY LOG REPORTS

- Track usage history through report logs

INTERNAL MEMORY

- Up to 200,000 total unique users/codes

- 100,000 history events

PROGRAMMABLE ACCESS CODES

- 3 to 6 digit code that can be used to strike one or both relays
- Not bound by set length. Each user can select any code from 3 to 6 digits long

TWO RELAY OUTPUT WITH PROGRAMMABLE STRIKE TIME

TWO PROGRAMMABLE CONTACT INPUTS

IMPORT DATABASE FROM EXCEL (CSV)

- Makes importing existing databases a breeze

SECURITY AND SAFETY

TAMPERING AND ACCESS

- Vandalism proof casing
- Security screws

FORCED ENTRY SENSOR WITH INTERNAL SIREN AND FAIL SECURE OUTPUT

- A numerical passcode is required before opening its enclosure

REAL-TIME DIAGNOSTICS

- Get real-time diagnostic information
- Remote automatic software updates

SPECIFICATIONS

WARRANTY

- 2 Year limited warranty

OPERATIONAL VOLTAGES

- 12V-16V AC/DC
- 12 Watts
- Solar Compatible

RELAY CONTACT

- 5 Amps

DIMENSIONS

- Height 8.5" x Width 12" x Depth 4.25"

OPERATING TEMPERATURE

- -40F to +167F