


# PB1100 PANIC BAR



### Features & Benefits

- Weather Resistant Rim Style Exit Device
- Grade 1 Certified ANSI/BHMA A156.3 Series
- Complies with A1117.1 ADA requirements
- UL/cUL Listed
- Fire Rated (FR) Available – UL/cUL Listed 3 hr. fire-rated 10C, UBC -2 (1997)



WEATHER RESISTANT

### Ordering Information

Part Number	Description
PB1100-AL	PB1100 Panic Bar
PB1100-SS	PB1100 Panic Bar, Stainless Steel
PB1100FRFIRE	PB1100 Panic Bar, Fire Rated
PB1142-42	PB1142 Panic Bar for 48" Doors
PB1142-SS	PB1142 Panic Bar for 48" Doors, Stainless Steel

### Dimensions & Specs

ANSI A156.3 SERIES GRADE 1 CERTIFIED. COMPLIES WITH A117.1 ADA REQUIREMENTS. DOOR THICKNESS: 1-3/4" (45MM) STANDARD. DEVICE LENGTH: 33" STANDARD, FOR 36". DOOR SIZE HANDING: NON-HANDED HEAD COVER: ZINC DIE-CASTED OR STAINLESS STEEL PUSH BAR: PLATED STEEL OR STAINLESS STEEL CHASSIS: PLATED STEEL OR STAINLESS STEEL SLIDE COVER: PLATED STEEL OR STAINLESS STEEL END CAP: PLATED STEEL OR STAINLESS STEEL LATCH BOLT: STAINLESS STEEL POWDER METALLURGY LATCH BOLT THROW: 11/16" (17MM) DEADLOCKING LATCH: STAINLESS STEEL POWDER METALLURGY DEADLOCKING LATCH THROW: 9/16" (14MM) DOGGING: 1/4" TURN HEX KEY DOGGING, STANDARD STRIKE: ZINC DIE-CASTED (AL) OR SOLID STAINLESS STEEL, WITH A PLATED ROLLER (SS/FR).

Visit [lockeyusa.com/warranty](http://lockeyusa.com/warranty) for full warranty details, information, and limitations.