

QR Reader

The QR Reader is equipped with a rugged, backlit keypad and is designed to withstand severe weather conditions. Built for applications that integrate QR and bar-code scanning, the QR Reader even offers the ability to unlock doors with proximity credentials and PINs, as well as the flexibility to configure two-factor authentication.

Model

PN: RDRQR

Specifications:

Input

QR
Bar Code
Prox
Frequency: 125 kHz
Read Range: up to 1.1"

Output

Wiegand protocol
Cable Distance: Wiegand 500' (22 AWG)

Environmental

Temperature: -4° ~ +140° F / -20° ~ +60° C
Humidity: 0 - 95% relative humidity non-condensing
Protection Rating: IP65

Enclosures

Dimensions: (W x H x D) 3.3" x 4.6" x .98"
Weight: 0.75 lbs / 12 oz / 340 g

Weight

0.75 lbs / 12 oz / 340 g

Power

12V DC (Linear power supply recommended)
Max Amperage: 200mA

Manufacturer's Limited Warranty

One to five-year warranty against defects in materials and workmanship. For full details, visit www.prodatakey.com/warranty

Visit www.prodatakey.com or www.prodatakey.zendesk.com to access marketing, installation, and support resources. For questions about PDK QR Reader, please contact support@prodatakey.com.

