

# PoE Accessories

## 1 to 2 CH PoE Extender (Repeater)

Model: PoER-02

Split 1Ch PoE to 2Ch and extend the PoE signal for additional 150 meters. Designed for applications where PoE camera or 2 are located over 100 meter distance from the PoE switch. Allows to transmit both camera's PoE signal over 1 Ethernet cable. This should simplify the installation, save on cabling cost and labor.



- Extends PoE Range Up To Additional 150 Meters
- 10/100Mbps Ethernet
- 1 Ch input / 2 Ch Output
- No Additional Power Supply Is Required\*
- Automatically Detects And Protects PoE Equipment From Being Damaged By Incorrect Installation
- Compliance With IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3af/at standards
- Wall Bracket/Earthling Terminal
- Rail (mail/female) design to attach several units in a row



\* Will cause a power loss of approx. 3 watt for its own operational use.

\* Power (Watt) supplied to the camera in the end of the line depends on: Number of cameras ,cable distance and quality, and PoE power input.

## Ethernet over Coax (EoC)

Model: EoC-01

Designed for applications where IP camera is replacing an existing Analog camera so the Coax cable and DC12V power infrastructure are already available.

- Full Set - Transmitter + Receiver
- Up To 150 Meter of Ethernet over Coax
- Up to 1.5m for each ethernet cable (Cat5e Standard)
- 10Mbps Ethernet
- Passive Units: No Power supply needed for the EoC-01.
- Requires that the camera will be powered on



## None PoE Power Over Ethernet Transmitter/Receiver

Model: DCoE-01

Designed To transmit DC Power and Ethernet Over Ethernet Cable.

- Full Set - Transmitter/Receiver
- 50 Meter working distance over standard Cat5e/6 cable
- Requires Camera External Power Supply
- Supply a DC Power Input To Camera and - not PoE

