

**K-2 SLIDE GATE  
OPERATOR**



**RESIDENTIAL**  
CLASS I VEHICULAR SLIDE GATE OPERATOR



**LCD DIAGNOSTICS DISPLAY**  
 - Displays full error messages  
 - Reads real-time voltages and settings

**DIGITAL LIMITS**

**REMOVABLE POWER SUPPLY**  
 - Convenient fuse access  
 - L.E.D status indicators  
 - Convenient power switch  
 - E-Z access power outlet  
 - E-Z set up 115V/230V  
 - Included low voltage option

**V FLEX CONTROL BOARD**  
 - Conveniently labeled enclosure  
 - Ergonomically located

**BUILT-IN HEATER**  
 - Cold weather operation  
 down to -20° F

**NEW REDESIGNED CHASSIS**

**COMPATIBLE WITH VIKING WIRELESS PRODUCTS**

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible hand held device.
- Plug & Play connection for the Viking wireless expansion products.

**BATTERY BACKUP INCLUDED**

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.

**LIGHTNING PROTECTION**

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps
- On-board surge protection monitoring.

**DIGITAL LIMITS**

- Simple, push button limit setup.
- Adaptive Digital Limit control maintains open and close limit position during changing environments and power failures.

**INTEGRATED HEATER**

- Built-in heater for operating temperatures down to -20° F.
- This will allow you run your operator in the coldest conditions.

**SOLAR SMART**

- Power Saving technology minimizes current draw while at standby.

**DIAGNOSTICS DISPLAY**

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

<b>Operational Voltage</b>	24 VDC
<b>Main Power Source Options</b>	120/240 VAC Single Phase
<b>Battery</b>	12 VDC x 2
<b>Battery Backup</b>	100 Full Contin. Cycles (700 lbs)

<b>Operating Speed</b>	12" per Second
<b>Operating Temperature</b>	-20°F up to +160°F
<b>Max Gate Capacity</b>	700 lbs/ 30'
<b>Max Duty Cycle</b>	100% Contin. Cycle