



9024 DC VEHICULAR SLIDE GATE OPERATOR

• RESIDENTIAL • COMMERCIAL



- Operator is 24 Volt DC and includes built-in battery backup
- 115/230 VAC (switch selectable) or 24 VDC Solar Power
- 1/2 HP Quadra Drive Heavy-duty DC Motor
- Adjustable limit nuts for precise gate limit control
- Easy to use manual T-handle release
- Heavy-duty gearbox
- 0.0 Amp SBPD Circuit (solar power only)
- Solar power ready
- Pad or post mount
- Heavy-duty steel frame
- 5-year limited warranty



easy to use
"T-Handle" release



quadra drive DC motor
for longer life



battery backup
built-in (7.2 AH battery x2)




full size gearbox
heavy-duty 30:1 ratio gearbox

9024 VEHICULAR SLIDE GATE OPERATOR

9024 1/2 HP Quadra Drive Motor

16.75" W x 28" H x 19" D (42.5cm W x 71cm H x 48.3cm D)



	CLASS OF OPERATION	MAX GATE LENGTH *	MAX GATE WEIGHT *	MOTOR	INPUT	MAXIMUM CYCLES
9024-080	I, II, III, IV	40 Ft (12.2 m)	1000 Lbs. (453.6 kg)	1/2HP Quadra Drive DC Motor	115 / 230 VAC 1.8 A / 0.9 A	Continuous with AC source 40 with 7.2 Ah backup battery power ^{1,2} 150 with 18 Ah backup battery power ^{1,2}
9024-081 (requires solar power input)	I, II, III, IV	40 Ft (12.2 m)	1000 Lbs. (453.6 kg)	1/2HP Quadra Drive DC Motor	24 VDC 8.5 A	150+ ^{1,2} with DK solar kit, unknown with systems / batteries provided by others

¹ Assumes gate is on level ground, in good condition with properly adjusted hardware.

² Assumes a 16 foot gate weighing 1000 Lbs. Other external factors (temperature, charge state of batteries, gate weight, gate length, etc.) will affect the performance of the gate operator and may reduce the number of cycles shown.

Technical Features

Mechanical

Frame: 3/16 steel, corrosion protected

Cover: 1/4 inch polyethylene

Reduction: belt driven 30:1 gear reduction running in a continuous oil bath

Speed: Approximately 1 ft/sec (30.5 cm/sec)

Chain: Unit is shipped with 20-ft of #40 roller chain

Manual Release: "T-Handle" release is easily accessible from front of operator

Operator re-connects automatically when handle is released

Options

Heater kit for cold weather environments
Can only be used with AC powered operators

Steel base plate for post mounting

18 Ah batteries (AC powered operator only)

Solar Kit (Includes two 18 Ah batteries and 10 Watt, 24 VDC solar panel)

Electrical

Adjustable partial open limit

Easy adjustable chain driven limit nuts

Auto-close timer 1-30 seconds

Selectable loop/reverse input function; stop or reverse

Anti-tailgating feature helps to control un-authorized traffic

Standard normally closed stop circuit

DC Power Shut-Off switch

Battery protection circuit

Ports for plug-in open and reverse loop detectors – DKS detectors only

Gate Tracker reporting output provides operator data to access control system (DKS 1833, 1835, 1837 or 1838 only)

AC Powered Operator Only

115 VAC Convenience outlets

AC Power Shut-Off switch

DC Powered Operator Only

0.0 Amp SBPDPatPend Circuit

Miscellaneous

Environmental: -10°F to 140°F (23°C to 62°C)

Thermostatically controlled heater kit required for operation below freezing temperatures to prevent batteries from freezing. Heater kit can only be used with AC powered operators.

Operator requires Type B1 or Type B2 entrapment protection devices with 10K resistive termination, otherwise the operator will not function

Shipping weight approximately 130-150 Lbs (59-68 kg)
Depending on model and options selected



Access Control Solutions since 1948

MEMBER:



DOORING®, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.

Tel: 310-645-0023 FAX: 310-641-1586 www.dooring.com

© 2016 All Rights Reserved. Product specifications may change without notice.
Rev. 6/16

Distributed by: